

# KERN PCB 200-3

**KERN**

The standard in the laboratory, ideal for a wide range of applications for Industry 4.0



## Category

Brand	KERN
Product category	Laboratory balance
Product group	Precision balance
Product family	PCB

## Measuring System

Weighing system	Strain gauge
Weighing capacity [Max]	200 g
Readability [d]	0,001 g
Reproducibility	0,001 g
Linearity	± 0,005 g
Resolution	200.000
Tare range	200 g

Adjustment options	Adjusting with external weight
Recommended adjusting weight	200 g (F1)
Possible calibration points	50 g; 100 g; 200 g
Stabilization time	3 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,006 g

USP Minimum weight of sample (k = 2, U = 0.1%)	2 g
Construction type of the scale	Single-range balance

## Units

kg  
g  
t  
gn  
dwt  
tl (Tw)  
tl (HK)  
ozt  
tl (Singap, Malays)  
ct

mo  
lb  
oz  
ffa  
m  
PCS  
%

Maximum creep (15 minutes)	10 mg
Maximum creep (30 minutes)	20 mg
Default unit	g

## Display

Display type	LCD
Display backlight	✓
Display screen size	89×30 mm
Display digit height	21 mm
Languages of the user interface	English Symbol language

## Construction

Dimension housing (W×D×H)	163×245×65 mm
Dimensions completely mounted (W×D×H)	163×245×123 mm
Dimensions ring-shaped draught shield - inner (Ø×H)	90×40 mm
Dimensions weighing surface (Ø)	82 mm
Dimensions weighing surface	82 mm
Material housing	plastic
Material weighing plate	plastic, with conductive lacquer
Material platform	plastic
Material draught shield	plastic
Material display housing	plastic
Level indicator	✓
Levelling feet adjustable	✓
Transport safety lock - bolt torque	0,4 Nm

## Functions

PreTare function	✓
Sum memory function	✓
Percentage determination	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	acoustically visual
Underfloor weighing	Hook (included in delivery)
Function for averaging under unstable weighing conditions	✓
Counting function	✓

# KERN PCB 200-3



The standard in the laboratory, ideal for a wide range of applications for Industry 4.0

Counting resolution (laboratory conditions)	100.000
Counting reference weight can be entered	✓
Smallest piece weight when piece counting - laboratory conditions	2 mg
Smallest piece weight when piece counting - normal conditions	20 mg
Reference quantity	5, 10, 20, 50, free, Input
Hold function	✓
IP protection - display	no IP protection
	5 min
	2 min
Auto-off interval(s) in battery mode/rechargeable battery mode	1 min
	30 min
	60 min
	30 sec
Auto-off interval(s) in mains power mode	off
Tare function	manual (multi)
Number of keys for operation	5

## Interface

Interfaces	RS-232 (optional) Bluetooth (optional) Ethernet (optional) USB-Device (optional) KUP WiFi (optional)
compatible with EasyTouch	✓

## Power Supply

Supplied power supply	Power supply & battery function (battery not included)
Power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO UK US CH
Input voltage power supply / power [Max]	100 V - 240 V AC, 50 / 60 Hz
Power supply cable removable	removable
Input voltage device / power [Max]	5,9V, 1A
Power socket for mains adapter	Hollow plug, inside plus, Ø outside 5,5 mm, Ø

	inside 2,1 mm, long 13 mm
Battery / accumulator type	Li-Ion
Battery connection	Battery insert
Battery operating time	20 h
Rechargeable battery operating time - backlight on	24 h
Rechargeable battery operating time - backlight off	48 h
Rechargeable battery charging time	8 h
Rechargeable battery optional	Rchrg. battery optional - intern

## Environmental conditions

Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Humidity of environment [Max]	80 %
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

## Approval

CE mark	✓
---------	---

## Services (optional)

Article number for DAkkS calibration	963-127
Article number for certificate of conformity	969-517

## Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	235×365×175 mm
Shipping method	Parcel service
Net weight approx.	1,00 kg
Gross weight approx.	1,6 kg
Shipping weight	3 kg

## Product information

GTIN/EAN number	4045761215610
REACH classification	no prohibited substances

# KERN PCB 200-3



The standard in the laboratory, ideal for a wide range of applications for Industry 4.0

## Pictograms

### STANDARD



### OPTION

