



Water baths

Code JDD001, JDD002, JDD003, JDD004

- Housing made of high-quality sheet steel, the surface of which is painted with a tough, durable coating. Stainless steel tank, made in one piece, free of welds. Removable stainless steel lid with holes and reducing rings. Includes support tray covering the heating element.
- Digital regulation of parameters. Continuous or timed operation. Sound signal at the end of the programmed time. Auto-adjustment function.
- Splash-proof control panel.
- No water or low water level detection system.
- Over-temperature protection. If the water temperature exceeds the set temperature by 5°C (modifiable value), the heating stops, the unit emits an audible signal and the alarm indicator lights up.
- With draining pump and side connector for drain hose (except model 601/3).



Specifications

Model	601/3	601/5	601/12	601/19
Code	JDD001	JDD002	JDD003	JDD004
Capacity (L)	3	5	12	19
Holes	1	2	4	6
Temperature range (°C)	RT+5 - 100			
Accuracy of temp. control (°C)	±1			
Display resolution (°C)	0,1			
Timer (min)	1 - 9999			
Draining pump	No	Yes	Yes	Yes
Tank size (mm) (LxWxH)	150x135x150	300x150x150	320x300x150	500x300x150
Power supply	220 – 240 V, 50/60 Hz			
Power (W)	300	600	1000	1500
Approx. weight (kg)	3	4	6	8